



| Terminal (K1) | | | |
|---------------|----|----|--------|
| Name | No | No | Name |
| VDD_BL | 2 | 1 | VDD_BL |
| VDD | 4 | 3 | VDD |
| VSS | 6 | 5 | VSS |
| /RD | 8 | 7 | /WR |
| RS | 10 | 9 | /CS |
| D14 | 12 | 11 | D15 |
| D12 | 14 | 13 | D13 |
| D10 | 16 | 15 | D11 |
| D8 | 18 | 17 | D9 |
| D6 | 20 | 19 | D7 |
| D4 | 22 | 21 | D5 |
| D2 | 24 | 23 | D3 |
| D0 | 26 | 25 | D1 |
| VSS | 28 | 27 | VSS |
| NC | 30 | 29 | NC |
| NC | 32 | 31 | NC |
| NC | 34 | 33 | NC |
| △ NC | 36 | 35 | NC △ |

- Note:
- *1. LCD Display Type: TFT, Transmissive
 - *2. Pixel Arrangement: RGB-SPRIPE
 - *3. Color Depth: 65k colors
 - *4. Logic Supply: 3.3V
 - *5. Backlight Supply: 5.0V
 - *6. Backlight: LEDs
 - *7. Operating Temperature: -20°C~70°C
 - *8. Storage Temperature: -30°C~80°C
 - *9. Environmental Standard: ROHS



| | | |
|-----------|------------------------------|--------------------|
| C | | |
| B | | |
| A | Typing Correction | K.C. 2011-09-26 |
| Rev | Note | Date |
| Dwg Title | LMT070DICFWD-NBN Outline Dwg | |
| Dwg No. | MK-003755a-1-1 | Date 2011-01-12 |
| Scale | Tol. | Unit |
| 1/1 | ±0.5 | mm |
| Approved | Checked | Paper Size A3 |
| | | Drawn Yang Lin |

TOPWAY