



LCD FPC Details
(Conductor side)
Scale=3/1

K1 Terminal	
No	Pin Name
1	LED_CATHODE
2	LED_CATHODE
3	LED_ANODE
4	LED_ANODE
5	NC
6	NC
7	NC
8	/RST
9	/SPEN
10	SPCK
11	SPDA
12	D0
:	:
35	D23
36	HSYNC
37	VSYNC
38	DCLK
39	NC
40	NC
41	VDD
42	VDD
43	NC
:	:
51	NC
52	DEN
53	GND
54	GND

Note:

- *1. LCD Display Type: TFT, Transmissive
- *2. Pixel Arrangement: RGB-SPRIPE
- *3. Operating Voltage : 3.3V
- *4. Viewing Direction : 12H
- *5. Backlight Supply : 20mA (19.2V TYP.)
- *6. Backlight : LEDs
- *7. Operating Temperature : -20°C~70°C
- *8. Storage Temperature : -30°C~80°C



C		
B		
A	Refine Outline	Yang 2012-01-31
Rev	Note	Date
Dwg	Title	
	LMT035KDH03 Outline Dwg	
Dwg No.	MK-003085a-1-1	Date 2009-09-25
Scale	Tol.	Unit
1/1	±0.5	mm
Approved	Checked	Paper Size A3
		Drawn ChengYuanyuan

TOPWAY