



K1 Terminal	
No	Pin Name
1	RX3+
2	RX3-
3	NC
4	FRC
5	GND
6	RXC+
7	RXC-
8	GND
9	RX2+
10	RX2-
11	GND
12	RX1+
13	RX1-
14	GND
15	RX0+
16	RX0-
17	LR
18	UD
19	VCC_IN
20	VCC_IN

K2 Terminal	
No	Pin Name
1	BL_Vi
2	BL_ADJ
3	BL_EN
4	BL_GND

- Note:
- \*1. LCD Display Type: TFT.Transmissive
  - \*2. Pixel Arrangement: RGB-SPRIPE
  - \*3. Operating Voltage : 3.3V
  - \*4. Backlight Supply : 12.0V
  - \*5. Backlight : White LED
  - \*6. K1: STARCONN 076B20-0048RA-G4 or equivalent
  - \*7. K2: LM123S004HTF13, 4PIN, UNE or equivalent
  - \*8. Operating Temperature : -20°C~70°C
  - \*9. Storage Temperature : -30°C~80°C



C		
B		
A	Revise Outline	Yang 2011-06-10 Date
Rev Note		
Dwg Title	LMT070DICFWD-NDN Outline Dwg	
Dwg No.	MK-003644a-1-1	Date 2011-05-25
Scale	1/1	Tol. ±0.5
Unit	mm	Paper Size A3
Approved	Checked	Drawn Yang Lin

